

Optronics®



LED WORK LIGHTS & LIGHT BARS

LED WORK LIGHTS

SMD LED TECHNOLOGY FOR LONG TERM RELIABILITY

LED LIFETIME WARRANTY

HEAVY DUTY CONSTRUCTION FOR DURABILITY AND PERFORMANCE

TLL70 FLOOD



4800 RAW
3360 EFFECTIVE
LUMEN OUTPUT

12V/24V **IP69K**



Contoured lens produces wide angle beam

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|------------------------|---------------|--------|----------|
| TLL70FB | TLL70FBP | Wide angle, flood beam | 12-24VDC | 6 SMD | 1 |

MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware
WT/DIMS 1.41 lbs. / 4.375" W x 5.375" H x 2.625" D
VOLT/AMP 12.8VDC - 2.8A, 24.0VDC - 1.43A [14-gauge, 10" lead and ground wire]
WARRANTY Lifetime LED Warranty

TLL64 FLOOD



3200 RAW
2240 EFFECTIVE
LUMEN OUTPUT

12V/24V **IP69K**

Ultrabright output in standard size light

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-------------|---------------|--------|----------|
| TLL64FB | TLL64FBP | Flood beam | 12-24VDC | 4 SMD | 1 |

MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware
WT/DIMS 1.41 lbs. / 4.187" W x 5.375" H x 3" D
VOLT/AMP 12.8VDC - 2.9A, 24.0VDC - 1.5A [14-gauge - 10" lead and ground wire]
WARRANTY Lifetime LED Warranty

TLL55 FLOOD



2160 RAW
1510 EFFECTIVE
LUMEN OUTPUT

12V/24V **IP69K**



Contoured design for wide angle beam

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-----------------------|---------------|--------|----------|
| TLL55FB | TLL55FBP | Wide angle flood beam | 12-24VDC | 9 SMD | 1 |

MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware
WT/DIMS 1.35 lbs / 4.87" x 5.75" x 2.03"
VOLT/AMP 12.8VDC - 1.5A, 24.0VDC - 0.73A
WARRANTY Lifetime LED Warranty

2160 RAW
1492 EFFECTIVE
LUMEN OUTPUT

12V/24V **IP69K**

Low profile design – less than 2.5 inches deep

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-------------|---------------|--------|----------|
| TLL46CFB | TLL46CFBP | Flood beam | 12-24VDC | 9 SMD | 3 |

MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware
WT/DIMS 1.764 lbs. / 5" x 7" x 2.375"
VOLT/AMP 12.8VDC - 1.65A, 24.0VDC - 1.0A [14-gauge, 10" lead and ground wire]
WARRANTY Lifetime LED Warranty



TLL46 FLOOD

2160 RAW
1346 EFFECTIVE
LUMEN OUTPUT

12V/24V **IP69K**

Trapezoid beam for ag or construction equipment

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|----------------|---------------|--------|----------|
| TLL46TB | TLL46TBP | Trapezoid beam | 12-24VDC | 9 SMD | 3 |

MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware
WT/DIMS 1.764 lbs. / 5" x 7" x 2.375"
VOLT/AMP 12.8VDC - 1.50A, 24.0VDC - .73A [14-gauge, 10" lead and ground wire]
WARRANTY Lifetime LED Warranty



TLL46 TRAPEZOID

2160 RAW
1484 EFFECTIVE
LUMEN OUTPUT

12V/24V **IP69K**

Spot beam for ag or construction equipment

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-------------|---------------|--------|----------|
| TLL54TB | TLL54TBP | Spot beam | 12-24VDC | 9 SMD | 5 |

MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware
WT/DIMS 1.51 lbs. / 5" x 7" x 2.375"
VOLT/AMP 12.8VDC - 1.50A, 24.0VDC - 0.73A [14-gauge, 10" lead and ground wire]
WARRANTY Lifetime LED Warranty



TLL54 SPOT


LED WORK LIGHTS

SMD LED TECHNOLOGY FOR LONG TERM RELIABILITY

LED LIFETIME WARRANTY

HEAVY DUTY CONSTRUCTION FOR DURABILITY AND PERFORMANCE

TLL71
FLOOD



2160 RAW | **1490** EFFECTIVE
LUMEN OUTPUT

12V/24V **IP69K**



Contoured lens produces wide angle beam

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-------------|---------------|--------|----------|
| TLL71FB | TLL71FBP | Flood beam | 12-24VDC | 9 SMD | 3 |

MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware
WT/DIMS 1.41 lbs. / 4" W x 5" H x 2.25" D
VOLT/AMP 12.8VDC - 1.43A, 24.0VDC - .66A [14-gauge - 10" lead and ground wire]
WARRANTY Lifetime LED Warranty

TLL72
FLOOD



2160 RAW | **1490** EFFECTIVE
LUMEN OUTPUT

12V/24V **IP69K**



Contoured lens produces wide angle beam

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-------------|---------------|--------|----------|
| TLL72FB | TLL72FBP | Flood beam | 12-24VDC | 9 SMD | 3 |

MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware
WT/DIMS 1.5 lbs. / 5" W x 5.375" H x 2.25" D
VOLT/AMP 12.8VDC - 1.43A, 24.0VDC - .66A [14-gauge - 10" lead and ground wire]
WARRANTY Lifetime LED Warranty

TLL73
FLOOD



2160 RAW | **1490** EFFECTIVE
LUMEN OUTPUT

12V/24V **IP69K**



Built-in handle and switch

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-------------|---------------|--------|----------|
| TLL73FB | TLL73FBP | Flood beam | 12-24VDC | 9 SMD | 3 |

MATERIALS Polycarbonate lens and handle, aluminum housing, stainless steel hardware
WT/DIMS 1.61 lbs. / 5" W x 7.5" H x 3.25" D
VOLT/AMP 12.8VDC - 1.43A, 24.0VDC - 0.66A [14-gauge - 10" lead and ground wire]
WARRANTY Lifetime LED Warranty

1920 RAW | **1295** EFFECTIVE
LUMEN OUTPUT

12V/24V **IP69K**

Low profile design – only 2 inches deep

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-------------|---------------|--------|----------|
| TLL45FB | TLL45FBP | Flood beam | 12-24VDC | 8 SMD | 3 |

MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware
WT/DIMS 1.39 lbs. / 4.5" W x 5.75" H x 2" D
VOLT/AMP 12.8VDC - 1.50A, 24.0VDC - .67A [14-gauge - 10" lead and ground wire]
WARRANTY Lifetime LED Warranty



TLL45
FLOOD

1440 RAW | **1028** EFFECTIVE
LUMEN OUTPUT

12V/24V **IP69K**

Low profile design – only 2 inches deep

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|-----------|--------------|-------------|---------------|--------|----------|
| TLL44FB | TLL44FBP | Flood beam | 12-24VDC | 6 SMD | 2 |
| TLL144FSL | Retail | Flood beam | 12-24VDC | 6 SMD | 3 |

MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware
WT/DIMS .98 lbs. / 4" W x 5.125" H x 2.375" D
VOLT/AMP 12.8VDC - 1.1A, 24.0VDC - .5A [14-gauge - 10" lead and ground wire]
WARRANTY Lifetime LED Warranty



TLL44
FLOOD

1440 RAW | **1036** EFFECTIVE
LUMEN OUTPUT

12V/24V **IP69K**

Low profile design – less than 2.5 inches deep

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-------------|---------------|--------|----------|
| TLL48FB | TLL48FBP | Flood beam | 12-24VDC | 6 SMD | 5 |

MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware
WT/DIMS 1.14 lbs. / 4.125" W x 5.281" H x 2.125" D
VOLT/AMP 12.8VDC - 1.52A, 24.0VDC - .5A [14-gauge - 10" lead and ground wire]
WARRANTY Lifetime LED Warranty



TLL48
FLOOD


LED WORK LIGHTS

SMD LED TECHNOLOGY FOR LONG TERM RELIABILITY

LED LIFETIME WARRANTY

HEAVY DUTY CONSTRUCTION FOR DURABILITY AND PERFORMANCE

TLL60 FLOOD



1440 RAW
865 EFFECTIVE
LUMEN OUTPUT

12V/24V

IP69K

Rectangular design – 6 inches wide by 2 inches high

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|---|--------------|-------------|---------------|--------|----------|
| TLL60FB | TLL60FBP | Flood beam | 12-24VDC | 6 SMD | 5 |
| MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware | | | | | |
| WT/DIMS .95 lbs. / 6" W x 3.25" H x 2.438" D | | | | | |
| VOLT/AMP 12.8VDC - 1.1A, 24.0VDC - .5A [14-gauge - 10" lead and ground wire] | | | | | |
| WARRANTY Lifetime LED Warranty | | | | | |

TLL51 FLOOD



800 RAW
560 EFFECTIVE
LUMEN OUTPUT

12V/24V

IP69K

Compact design – only 2 inches square

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|--|--------------|-------------|---------------|--------|----------|
| TLL51FB | TLL51FBP | Flood beam | 12-24VDC | 1 SMD | 10 |
| TLL51FRPG | TLL51FRPGP | Flood beam | 12-24VDC | 1 SMD | 10 |
| MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware | | | | | |
| WT/DIMS .37 lbs. / 2" W x 3" H x 2.5" D | | | | | |
| VOLT/AMP 12.8VDC - .85A, 24.0VDC - .41A [14-gauge - 10" lead and ground wire] | | | | | |
| WARRANTY Lifetime LED Warranty | | | | | |

TLL52 FLOOD



720 RAW
464 EFFECTIVE
LUMEN OUTPUT

12V/24V

IP69K

Compact design – only 2.75 inches square

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|--|--------------|----------------------------|---------------|--------|----------|
| TLL52FB | TLL52FBP | Flood beam | 12-24VDC | 3 SMD | 10 |
| TLL52FWB | TLL52FWBP | Flood beam, white housing | 12-24VDC | 3 SMD | 10 |
| TLL152FSL | Retail | Flood beam, retail package | 12-24VDC | 3 SMD | 3 |
| MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware | | | | | |
| WT/DIMS .38 lb. / 2.75" W x 4" H x 1.687" D | | | | | |
| VOLT/AMP 12.8VDC - .6A, 24.0VDC - .3A [14-gauge - 10" lead and ground wire] | | | | | |
| WARRANTY Lifetime LED Warranty | | | | | |

324 RAW
252 EFFECTIVE
LUMEN OUTPUT

12V/24V

IP69K

Lightweight, compact LED work light

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|--|--------------|-------------|---------------|--------|----------|
| TLL50FB | TLL50FBP | Flood beam | 12-24VDC | 9 SMD | 3 |
| TLL150FSL | Retail | Flood beam | 12-24VDC | 9 SMD | 3 |
| MATERIALS Polycarbonate lens, polycarbonate housing, stainless steel hardware | | | | | |
| WT/DIMS .96 lbs. / 4.938" W x 5.75" H x 2.375" D | | | | | |
| VOLT/AMP 12.8VDC - .53A, 24.0VDC - .28A [22-gauge, 10" lead and ground wire] | | | | | |
| WARRANTY Lifetime LED Warranty | | | | | |



TLL50 FLOOD


20000 RAW
11600 EFFECTIVE
LUMEN OUTPUT

12V/24V

IP65

50" light supplied in color retail window box

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|---|--------------|-----------------|---------------|--------|----------|
| UCL25CB | Retail | Spot/flood beam | 12-24VDC | 96 SMD | 1 |
| MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware | | | | | |
| WT/DIMS 8.1 lbs. / 50" x 3" x 3.5" | | | | | |
| VOLT/AMP 12.8VDC - 22.9A / 24VDC - 11.9A | | | | | |
| WARRANTY Lifetime LED Warranty | | | | | |



UCL25 FLOOD/ SPOT

12600 RAW
6777 EFFECTIVE
LUMEN OUTPUT

12V/24V

IP65

33" light supplied in color retail window box

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|---|--------------|-----------------|---------------|--------|----------|
| UCL22CB | Retail | Spot/Flood beam | 12-24VDC | 60 SMD | 1 |
| MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware | | | | | |
| WT/DIMS 5.625 lbs / 33" x 3.15" x 3.46" | | | | | |
| VOLT/AMP 12VDC - 9.8A / 24VDC - 5.7A | | | | | |
| WARRANTY Lifetime LED Warranty | | | | | |



UCL22 FLOOD/ SPOT


LED WORK LIGHTS

SMD LED TECHNOLOGY FOR LONG TERM RELIABILITY

LED LIFETIME WARRANTY

HEAVY DUTY CONSTRUCTION FOR DURABILITY AND PERFORMANCE

UCL20 FLOOD/ SPOT



7500 RAW
4521 EFFECTIVE
LUMEN OUTPUT

12V/24V


IP65

22" light supplied in color retail window box

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-----------------|---------------|--------|----------|
| UCL20CB | Retail | Spot/Flood beam | 12-24VDC | 40 SMD | 1 |

| | |
|-----------|--|
| MATERIALS | Polycarbonate lens, aluminum housing, stainless steel hardware |
| WT/DIMS | 4.8 lbs / 21.26" x 3.07" x 3.39" |
| VOLT/AMP | 12.8VDC - 6.8A / 24VDC - 3.1A |
| WARRANTY | Lifetime LED Warranty |

UCL32



7200 RAW
4000 EFFECTIVE
LUMEN OUTPUT

12V/24V


IP65

30" light with central white LEDs produce bright flood beam, red LEDs on left and right ends provide supplemental turn function (rear facing)

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|-----------|--------------|-------------|---------------|--------|----------|
| UCL32CTDB | N/A | Flood/Turn | 12-24VDC | 18 SMD | 1 |

| | |
|-----------|--|
| MATERIALS | Polycarbonate lens, aluminum housing, stainless steel hardware |
| WT/DIMS | 4.8 lbs / 29.6" x 2.3" x 2.875" |
| VOLT/AMP | 12.8VDC - 6.8A / 24VDC - 3.1A |
| WARRANTY | Lifetime LED Warranty |

UCL21 FLOOD/ SPOT



5000 RAW
2700 EFFECTIVE
LUMEN OUTPUT

12V/24V

IP65

13" light supplied in color retail window box

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-----------------|---------------|--------|----------|
| UCL21CB | Retail | Spot/Flood beam | 12-24VDC | 24 SMD | 1 |

| | |
|-----------|--|
| MATERIALS | Polycarbonate lens, aluminum housing, stainless steel hardware |
| WT/DIMS | 3.19 lbs / 13.58" x 3.15" x 3.46" |
| VOLT/AMP | 12.8VDC - 4A / 24VDC - 1.8A |
| WARRANTY | Lifetime LED Warranty |

2520 RAW
1550 EFFECTIVE
LUMEN OUTPUT


12V/24V

IP65

9" light supplied in color retail window box

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-----------------|---------------|--------|----------|
| UCL23CB | Retail | Spot/Flood beam | 12-24VDC | 12 SMD | 1 |

| | |
|-----------|--|
| MATERIALS | Polycarbonate lens, aluminum housing, stainless steel hardware |
| WT/DIMS | 2.4 lbs / 7.25" x 3" x 3.5" |
| VOLT/AMP | 12.8VDC - 3A / 24VDC - 1.5A [Hard wired, 16-inch leads] |
| WARRANTY | Lifetime LED Warranty |



UCL23 FLOOD/ SPOT

1800 RAW
780 EFFECTIVE
LUMEN OUTPUT


12V/24V

IP65

3" cube design light supplied in color retail window box

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|---------------|---------------|--------|----------|
| UCL24CB | Retail | Post mount | 12VDC | 6 SMD | 1 |
| UCL24CFB | Retail | Recess flange | 12VDC | 6 SMD | 1 |
| UCL24CRB | Retail | Recess flange | 12VDC | 12 SMD | 12 |

| | |
|-----------|---|
| MATERIALS | Polycarbonate lens, aluminum housing, stainless steel hardware |
| WT/DIMS | Post: 1.2 lbs 3.25" x 3" x 2.75" Recess Flange: 1.2 lb / 4.25" x 3.625" x 2.75" |
| VOLT/AMP | 12.8VDC - 1.4A |
| WARRANTY | Lifetime LED Warranty |



UCL24 FLOOD/ SPOT

1200 RAW
640 EFFECTIVE
LUMEN OUTPUT


12V/24V

IP67

UCL26CS supplied in color retail window box

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|-----------|--------------|-------------|---------------|--------|----------|
| UCL26CB | UCL26CBP | Post mount | 12-24VDC | 6 SMD | 24 |
| UCL26CEDB | UCL26CEDBP | Post mount | 12-24VDC | 6 SMD | 1 |
| UCL26CS | Retail | Post mount | 12-24VDC | 6 SMD | 6 |

| | |
|-----------|--|
| MATERIALS | Polycarbonate lens, aluminum housing, stainless steel hardware |
| WT/DIMS | 1.0 lb / 6.25" x 1.8" x 2"D |
| VOLT/AMP | 12/24VDC - 1.25A at 12.8V; 0.67A at 24V |
| WARRANTY | Lifetime LED Warranty |




UCL26 FLOOD

LED WORK LIGHTS

SMD LED TECHNOLOGY FOR LONG TERM RELIABILITY

UCL28 FLOOD/ SPOT



1800 RAW
1400 EFFECTIVE
LUMEN OUTPUT
UCL29CB

12V/24V

IP65


1100 RAW
770 EFFECTIVE
LUMEN OUTPUT
UCL28CS

UCL28CS supplied in color retail window box

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-------------|---------------|--------|----------|
| UCL28CS | Retail | Spot beam | 12-24VDC | 6 SMD | 3 |
| UCL29CB | UCL29CBP | Spot beam | 12-24VDC | 6 SMD | 12 |

MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware
WT/DIMS 0.89 lbs. - 3.74" x 3.15" x 2.52"
VOLT/AMP 12/24VDC - 0.81A at 12.8V; 0.43A at 24V
WARRANTY Three Year Warranty

UCL42 SPOT



1000 RAW
465 EFFECTIVE
LUMEN OUTPUT

12V/24V


IP67

45 degree angle - supplied in color retail window box

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-------------|---------------|--------|----------|
| UCL42CB | UCL42CBP | Angled beam | 12-24VDC | 6 SMD | 20 |
| UCL42CS | Retail | Angled beam | 12-24VDC | 6 SMD | 3 |

MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware
WT/DIMS 1 lb. / 4.33" x 2" x 1.38"
VOLT/AMP 12.8VDC - 3A / 24VDC - 1.5A
WARRANTY Lifetime LED Warranty

TLL41 FLOOD



1920 RAW
1030 EFFECTIVE
LUMEN OUTPUT

12V/24V

IP69K

Sealed LED light assembly in heavy duty rubber housing

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-------------|---------------|--------|----------|
| TLL41FS | Retail | Flood beam | 12-24VDC | 7 SMD | 3 |

MATERIALS Rubber housing, polycarbonate lens
WT/DIMS 1.16 lbs. / 4.85 diameter, 2.85" deep
VOLT/AMP 12/24VDC - 1.19A at 12.8V; 0.63A at 24V [Hard wired, 7-in. leads]
WARRANTY Three Year Warranty

INDUSTRY LEADING WARRANTY

HEAVY DUTY CONSTRUCTION FOR DURABILITY AND PERFORMANCE

3800 RAW
1988 EFFECTIVE
LUMEN OUTPUT

12V/24V

IP67




TLL42 FLOOD

Adjustable mounting arm with two swivel points

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-------------|---------------|--------|----------|
| TLL42FS | Retail | Flood beam | 12-24VDC | 13 SMD | 3 |

MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware
WT/DIMS 1.6 lbs. / 5" dia x 8" tall x 2.5" deep
VOLT/AMP 12/24VDC 3.25A at 12.8V; 1.63A at 24V
WARRANTY 3 Year Warranty



1800 RAW
900 EFFECTIVE
LUMEN OUTPUT

12V/24V

IP67




TLL145 FLOOD

Supplied in color retail window box

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-------------|---------------|--------|----------|
| TLL145FS | Retail | Flood beam | 12-24VDC | 7 SMD | 3 |

MATERIALS Polycarbonate lens
WT/DIMS 0.89 lbs. / 3.938" x 4.75" x 2.5"
VOLT/AMP 12/24VDC - 1.19A at 12.8V; 0.63A at 24V [Hard wired, 16-in. leads]
WARRANTY Three Year Warranty



1340 RAW
1080 EFFECTIVE
LUMEN OUTPUT

12V/24V

IP67




TLL153 FLOOD

Pair of 9-LED 2.75" square lights - supplied in color retail window box

| BULK P/N | POLYPACK P/N | DESCRIPTION | VOLTAGE RANGE | DIODES | CASE QTY |
|----------|--------------|-------------|---------------|--------|----------|
| TLL153FK | Retail | Flood beam | 12-24VDC | 9 SMD | 2 |

MATERIALS Polycarbonate lens, aluminum housing, stainless steel hardware
WT/DIMS 0.55 lbs. / 2.75" x 3.438" x 1.5"
VOLT/AMP 12/24VDC - 1.19A at 12.8V; 0.63A at 24V [Hard wired, 16-in. leads]
WARRANTY Three Year Warranty



ACCESSORIES



DISPLAYS



Z2150LWL



Z2120



ZH2018WL



For more information, scan this
QR code with your mobile device

www.optronicsinc.com

ZH2023WL